

F12643

300KG BACKSAVER CRANE WITH EXTENDED BOOM

Backsaver Crane:

- Max extended height = 1960 vertical
1526 horizontal at 200kg S.W.L
- Min extended height = 1460 vertical
1770 horizontal at 150kg S.W.L
- Max retracted height = 1687 vertical
1126 horizontal at 300kg S.W.L
- Min retracted height = 1300 vertical
1330 horizontal at 250kg S.W.L

8000 Series Brake Winch as supplied:

Model: F18230
 Gear Ratio: 5:1
 Application: Lifting
 Rated Capacity: 300kg (2940N)
 Mass (Winch only): 6kg
 Type of Brake: Self Actuating
 Drum Diameter: 50mm
 Flange Diameter: 130mm
 Drum Width: 52mm
 Cable size: Ø5mm
 Maximum Cable Capacity: 15m x Ø5mm
 Max. Effort on handle at Rated Load: 26kg
 Cable Breaking Strain: 1855kg
 Cable (Galv) as supplied: 7.5m x Ø5mm
 Fastening Device: Snap Hook

Notes:

- Recommended for lifting applications.
- Webbing cannot be used on these winches.
- Self actuating brake requires a minimum of 18kg to operate safely.
- Jarrett Winches and Cranes are not designed for the movement of people.



F13643W
 (300KGS BACKSAVER CRANE (WHITE)
 WITH EXTENDED BOOM)



F12643G
 (300KG GALVANISED BACKSAVER
 CRANE WITH EXTENDED BOOM)

F12643GR
 (300KG GALVANISED
 BACKSAVER CRANE EXTENDED
 BOOM WITH 7.5M ROPE)

